

Protective Agent

Protective Agent.

A liquid, neutral pH protective agent which is normally applied at the end of a car washing cycle. Active Wax is formulated to help preserve the car's freshly cleaned finish for a time, (until the next regular wash cycle).

Effective against: Dirt, insect fluids and other normal soil that occurs in an automotive environment, such as traffic.

Field of use:

- Self-Service Car Wash stations
- Drive-Thru and Tunnel Car Washes
- Home use with suitable application equipment (e.g. A high pressure washer)
- Auto "detailing" or restoration applications

Product benefits:

- Makes the next car washing cycle quicker and. " Provides a high-glossfinish.
- Contains wetting agents which help prevent spotting of the finish when the water is not completely "soft".
- Applied at a low concentration for economical use.

Description:

For care and quick drying of vehicles in self-service and brush washing installations.

Application:

- **Car Washes with Brushes:** Using metering pumps, set to apply in the proper cycle, for between 1:500 (0,2%) to 1:1000 (0,1%).
- **High Pressure Washers:** To be applied at a rate of between 1:500 (0,2%) to 1:1000 (0,1%). This will require pre-mixing before it is poured in the machine's detergent tank, for economical application. The following simplified formula will provide suitable dosing in most machines: Detergent / PreMix water X Injector Percentage setting = Applied Percentage. (For example: 1L deterg. / 10 L water X 5% = 0,5%).
- For best results, gently wipe the vehicle with a chamois after washing.
- Do not apply to HOT painted surfaces or allow the solution to dry on the vehicle.

- Standard equipment

Model	ALTO ACTIVE WAX 10 L	ALTO ACTIVE WAX 25 L
Ref. no.	81177	81222
Technical specifications		
Packaging	10 L	25 L
Ph value	3 (1% solution)	3 (1% solution)

- Standard equipment. ○ Supplementary accessories. □ Mountable equipment